



CERT

DVGW type examination certificate

DVGW-Baumusterprüfzertifikat

DG-4602CO0521

Registration Number
Registriernummer

Field of Application <i>Anwendungsbereich</i>	products of gas supply <i>Produkte der Gasversorgung</i>
Owner of Certificate <i>Zertifikatinhaber</i>	Haci Ayvaz End. Mamüller San.ve Tic. A.S Atatürk San.Bolg. Inan Cad. No. 44, TR-34555 Hadimköy / Istanbul
Distributor <i>Vertreiber</i>	Haci Ayvaz End. Mamüller San.ve Tic. A.S Atatürk San.Bolg. Inan Cad. No. 44, TR-34555 Hadimköy / Istanbul
Product Category <i>Produktart</i>	gas installation components : Stainless steel conducting (4602)
Product Description <i>Produktbezeichnung</i>	Stainless steel pliable corrugated tubing kit with flat sealing connections
Model <i>Modell</i>	Indoor-Flex
Test Reports <i>Prüfberichte</i>	factory control test: K 18/01/1890 from 01.02.2018 (DBI)
Test Basis <i>Prüfgrundlagen</i>	DVGW G 5616 (01.04.2012) DIN EN 15266 (01.08.2007)

Date of Expiry / File No. 16.04.2023 / 18-0099-GNV
Ablaufdatum / Aktenzeichen

13.04.2018 Kö A-1/2 *v. A.* 

Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

DVGW CERT GmbH is an accredited body by DAkkS according to DIN EN ISO/IEC 17065:2013 for certification of products for energy and water supply industry.

DVGW CERT GmbH ist von der DAkkS nach DIN EN ISO/IEC 17065:2013 akkreditierte Stelle für die Zertifizierung von Produkten der Energie- und Wasserversorgung.



DVGW CERT GmbH
Zertifizierungsstelle

Josef-Wirmer-Str. 1-3
53123 Bonn

Tel. +49 228 91 88 - 888
Fax +49 228 91 88 - 993

www.dvgw-cert.com
info@dvgw-cert.com

Gas Category <i>Gasart</i>	Remarks <i>Bemerkungen</i>
fuel gases according to G260	and DIN EN 437

Type <i>Typ</i>	Technical Data <i>Technische Daten</i>	Remarks <i>Bemerkungen</i>
Indoor-Flex	nominal diameter: DN 12 max. operating pressure: 0,5 bar	
Indoor-Flex	nominal diameter: DN 15 max. operating pressure: 0,5 bar	
Indoor-Flex	nominal diameter: DN 20 max. operating pressure: 0,5 bar	
Indoor-Flex	nominal diameter: DN 25 max. operating pressure: 0,5 bar	
Indoor-Flex	nominal diameter: DN 32 max. operating pressure: 0,5 bar	

certified Components
zertifizierte Bauteile / Werkstoffe

Registr. No. <i>Registrier-Nr.</i>	Component <i>Bauteil (Produktart)</i>	Model/Type <i>Modell/Typ</i>	Manufacturer <i>Hersteller</i>
NG-5124AQ1558	Flat sealing materials on graphit basis	novaphit@SSTC P3/novaphit@SSTC P3	Frenzelit GmbH

Hints of Utilization / Remarks
Verwendungshinweise / Bemerkungen

Connections of the end-connectors: thread according to DIN EN 10226-1
 Material: stainless steel 1.4404 or 1.4541
 Temperature range: -40°C up to +60°C
 The requirements of the Higher Thermal Resistance (HTB) are fulfilled.
 Further test reports:
 DBI in Freiberg:
 Type test report B 13/04/1614 dated 16.04.2013
 Supplementary test report B 15/01/1890 of 06.01.2015